



BDT Pty Ltd. Trading as **Rockstar Sealing Systems** ABN 18 085 322 390.
Head Office 3 Spray Avenue, Mordialloc 3195 Victoria, Australia.
Phone 1300 884 418 (03) 9580 5510 **Fax** (03) 9580 5530
Web www.rockstarsealing.com.au **Email** info@rockstarsealing.com.au

ANTI-SLIP

DESCRIPTION

Rockstar **ANTI-SLIP** is a treatment that increases the coefficient of friction of wet floor surfaces. The treatment is not a coating and will not change the appearance of the surface.

USES

ANTI SLIP is used in any area that becomes slippery due to water being on the floor. Floor areas in showers, pool surrounds, saunas, gymnasiums, bathrooms, foyers and kitchens typically are subjected to incidental water on the floor which poses a dangerous slipping hazard. Application of **ANTI SLIP** onto vitrified tiles, polished granite, glazed tiles, terrazzo and other hard mineral floor surfaces will increase the wet grip and thus reduce the possibility of falls and injuries.

ANTI SLIP should only be applied by qualified Rockstar applicators.

BENEFITS

- Dramatically reduces the slipperiness of wet floors
- Lasts up to 5 years even in high traffic areas
- Does not change the appearance of the surface
- Compatible with subsequent penetrating sealers
- Is not a surface coating, cannot flake or peel

PROPERTIES

Appearance and colour.....	Colourless to slightly yellow aqueous liquid
pH	2
Specific Gravity (Water = 1)	Approx. 1 g/ml
Boiling Point	100°C
Solubility in Water	Miscible
Flash Point	Non flammable

APPLICATION INSTRUCTIONS

- 1) Always apply first to an inconspicuous area or scrap piece of tile or stone to determine the residence time required to achieve the required level of slip reduction, and to ensure the suitability of this product for your substrate.
- 2) Ensure the surface to be sealed is clean, dry and free of any oils and other surface contaminants.
- 3) Carefully pour **ANTI SLIP** undiluted onto the floor and spread the liquid around using a squeegee applicator. Work carefully and slowly to ensure that there are no splashes or runs onto surfaces not being treated. Treat no more than 20 Mt² at a time.
- 4) Allow the product to remain on the floor for the time period as determined in step (1) above. Ensure that the surface remains wetted with product during the treatment period.
- 5) Remove excess material with a wet vacuum cleaner and wash the floor with Rockstar **NEUTRAL CLEANER**.
- 6) Once dry, all surfaces should be sealed with Rockstar **NATURAL FINISH STONE SEALER**.

COVERAGE

Coverage is dependent on the permeability of the flooring surface and is in the range of 5– 10 Mt² per litre.

PRECAUTIONS

- 1) **ANTI SLIP** should only be applied by qualified Rockstar applicators.
- 2) This product is corrosive and contains Fluoride; avoid contact with skin and eyes by wearing suitable protective gloves and eyewear.
- 3) Avoid contact of **ANTI SLIP** with aluminium and other metal surfaces.

CLEANING

Clean all equipment in water.

PACKAGING

ANTI SLIP is available in 1, 5 and 20 litre packs.

STORAGE

Keep container tightly closed when not in use.

Store in a cool, dry place out of reach of children.

DISCLAIMER

The advice and information contained herein is based on our best knowledge of the product. We believe the information to be accurate and reliable as at the date supplied, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, reliability, or completeness of the advice and information. We urge persons receiving this advice and information to make their own determination as to the advice and information's suitability and completeness for their own particular situation. When in doubt it is always prudent to perform a trial on a scrap section of material, or inconspicuous section of the job to ascertain the products suitability.